

Air Line Equipment

Fitter / Regulator / Micro-fog Lubricators Combination Set (Medium Duty)



Order No: M-FRML

Medium Duty Inlet Pressure: 0-17 Bar
 Port Size: 1/4, 3/8, 1/2, 3/4,
 1, 1 1/4, 1 1/2,
 Range: 0.3-10 Bar



Order No: PAF

High efficiency oil removal filter
 Coalescing element removes
 sub-micron particles and converts oil
 and water mist to liquid form to drain
 away.
 Operating pressure: 0-17 Bar
 Remaining oil content: 0-01 mg/m³
 particle removal: 0-0.1 µm
 Port Size: 1/4, 3/8, 1/2, 3/4,
 1, 1 1/4, 1 1/2



Order No: M-FRL

Medium Duty Inlet Pressure: 0-17 Bar
 Port Size: 1/4, 3/8, 1/2, 3/4,
 1, 1 1/4, 1 1/2,
 Range: 0.3-10 Bar

**Filters-regulator/
 lubricators**

'Puralre®' oil removal filters



Order No: UF

High efficiency oil vapour removal filter
 Dual function type incorporating an oil
 removal element (bottom) and an oil
 vapour removal element (top)
 Operating pressure: 0-17 Bar
 Remaining oil content: 0-0003 mg/m³
 at +21°C
 particle removal: 0-0.01 µm
 Port Size: 1/4, 3/8, 1/2, 3/4, 1.



Order No: MFL

Medium Duty Inlet Pressure: 0-17 Bar
 Port Size: 1/4, 3/8, 1/2, 3/4,
 1, 1 1/4, 1 1/2,
 Range: 0.3-10 Bar

Filters / lubricators

'Ultralre®' oil vapour removal filters



Order No: ML

Micro-fog plug in lubricator for general
 purpose.
 Port Size: 1/4, 3/8, 1/2, 3/4,
 1, 1 1/4, 1 1/2.



Order No: MFR

Medium Duty Inlet Pressure: 0-17 Bar
 Port Size: 1/4, 3/8, 1/2, 3/4,
 1, 1 1/4, 1 1/2,

Filters / regulators

Lubricators

Order No: MOFL

Micro-fog and oil fog for heavy duty
 lubrication
 Port Size: 3/4-1 1/2.



Order No: MF

Medium Duty Inlet Pressure: 0-17 Bar
 Port Size: 1/4, 3/8, 1/2, 3/4,
 1, 1 1/4, 1 1/2,

Filters



Order No: MR

Diaphragm and balanced valve design
 for good regulation.
 Inlet pressure: 0-17 bar (Type A)
 0-20 bar (Type B)
 Port Size: 1/4, 3/8, 1/2, 3/4,
 1, 1 1/4, 1 1/2.

Pressure regulators

Order No: MRV

Pressure relief valve for protect
 compressed air systems from over-
 pressurisation. High relief capacity
 sensitive and accurate threaded relief
 port for silencer or pyed exhaust.
 Adjusting Range: 0.3-4 bar
 0-10 bar
 Port Size: 1/4, 3/8, 1/2, 3/4,
 1, 1 1/4, 1 1/2.



Relief valves