

All Type of Turnbuckles



**G-225
HOOK
AND EYE**
Meets Federal
Specifications
FF-T-791b
Type 1 Form
1 — CLASS 6



**G-226
EYE & EYE**
Meets Federal
Specifications
FF-T-791b
Type 1 Form
1 — CLASS 4



**G-223
HOOK &
HOOK**
Meets Federal
Specifications
FF-T-791b
Type 1 Form
1 — CLASS 5



**G-227
JAW & EYE**
Meets Federal
Specifications
FF-T-791b
Type 1 Form
1 — CLASS 8



**G-228
JAW &
JAW**
Meets Federal
Specifications
FF-T-791b
Type 1 Form
1 — CLASS 7

Hot dip galvanized forged steel quenched & tempered.
Outstanding design features include elongated turn-
buckle eyes. Shackles one size smaller than turn-
buckles can be reeved through turnbuckle eye. Mod
thread an exclusive supabuckle feature.

SUPABUCKLE® THE TURNBUCKLE WITH THE MOD THREAD

Diameter And Take Up Inches	Average Overall With Ends in Closed Position Inches	WEIGHT POUNDS EACH		
		223-225 226 with Eyes or Hooks	G 227 Jaw and Eye	G 228 Jaw and Jaw
¼ x 4	8¼	.31	.32	.36
5/16 x 4½	9 ⁹ / ₁₆	.41	.47	.52
¾ x 6	11 ⁷ / ₈	.71	.76	.81
½ x 6	13 ⁵ / ₁₆	1.45	1.53	1.61
9	16 ⁵ / ₁₆	1.68	1.71	1.74
12	19 ⁵ / ₁₆	2.00	2.06	2.11
5/8 x 6	15½	2.35	2.35	3.02
9	18½	2.88	3.06	2.88
12	21½	3.78	3.78	3.38
¾ x 6	17	3.64	3.87	4.11
9	20	4.31	4.30	5.10
12	23	5.08	5.36	5.65
18	29	6.29	6.57	6.86
7/8 x 12	24 ³ / ₈	7.35	7.76	8.17
18	30 ⁵ / ₈	9.35	9.24	9.13
1 x 6	20 ³ / ₈	8.53	8.92	9.32
12	26 ³ / ₈	11.23	11.20	11.18
18	32 ³ / ₈	13.23	13.30	14.60
24	38 ³ / ₈	16.58	16.30	17.30
1¼ x 12	29 ⁷ / ₈	17.90	19.40	20.91
18	35 ⁷ / ₈	22.85	24.18	25.50
24	41 ⁷ / ₈	26.77	28.40	28.70
1½ x 12	32 ⁷ / ₈	27.94	28.99	30.05
18	38 ⁷ / ₈	33.19	32.38	31.56
24	44 ⁷ / ₈	37.69	39.18	40.67
1¾ x 18	41 ³ / ₄	50.88	49.16	55.04
24	47 ³ / ₄	58.00	60.68	63.36
2 x 24	51 ³ / ₄	89.80	94.60	100.00
2½ x 24	58½	140.00	150.00	161.00
2¾ x 24	61½	194.00	200.00	216.00

Jaw End Fittings, sizes
¼" through ¾" have Bolts
and Nuts. Jaw End Fittings,
sizes ¾" through 2¼" have
Pins and Cotters.
Galvanized Lock Nuts avail-
able for all sizes — R.H.
G4060, L.H. — G4061.

Hooks not supplied on sizes
larger than 1½".