

Bimetal thermometer (stainless steel)



Order No T-03
(back center)



Order No T-04
(bottom connection)

Dial face diameter : OD 50mmø, 63mmø, 75mmø, 100mmø
Range : -20-60°C, 0-120°C, 0-160°C
Connection 3/8 BSP, 1/2 BSP
Stem Length 50mm, 63mm, 75mm, 100mm

When ordering please state order No dial face, range temperature, connection & stem length

Remote Sensing Dial Thermometer

Type T-05 back connection

Type T-06 bottom connection

Material : steel case c/w 1.5 or 3 meter PVC covered capillary
stainless steel case c/w 1.5 or 3 meter stainless steel capillary

Dial face diameter : OD 60mm, OD80mm, OD100mm

Temperature range : -40-40°C, 0-120°C, 0-350°C

Stem length : 50mm, 63mm, 75mm, 100mm

When order please state order No dial face, temperature range, connection & stem length



Thermometer Stick

Order No: T-07



Note:

For spirit filled order No T-07A

For mercury filled order No T-07B

Total - length 305mm

Type :

A) red spirit filled

Range : -10/50°C, -10/110°C, -10/150°C, 0/240°F

B) mercury filled

Range -10/50°C, -10/110°C, -10/150°C, -10/360°C, -10/400°C, 0/240°F



Vline thermometer




Straight Type
Order No: T01



90° Angle Type
Order No: T02



Body Length



Tube Length

All Connection 3/8 or 1/2 BSP

Order No	Body Length L (mm)	Tube Length TL (mm)
T01-4-30L	110	30
T01-4-63L	110	63
T01-4-100L	110	100
T01-6-63L	150	63
T01-8-63L	200	63
T01-8-1-100L	200	100
T02-4-30L	110	30
T02-4-63L	110	63
T02-6-63L	150	150

	Temperature Range
A	-30-50°C
B	0-100°C
C	0-120°C
D	0-160°C
E	0-200°C
F	0-300°C
G	0-400°C
H	0-500°C
I	0-600°C

Note : below 200oC spirit filled
above 200oC mercury filled

When ordering please state type, body length, tube length and temperature range
Example : straight type, 200mm body length, 63mm tube length, 0-200oC Order No : T01-8-63L-E