

# All Type of MRO Chemicals



## Nickel Anti-Seize

- Prevents seizure up to 2600°F (1427°C)
- Does not contain lead, copper or graphite
- Protects against seizure, rust, and corrosion
- Chemically inert
- Acid resistant
- Can be used with ammonia, acetylene, and vinyl monomers which are unstable in the presence of copper
- Strong resistance to water washoff
- Brushable to -18°F (0°C)
- Will not run, drip or settle out
- Silver color

Meets or exceeds these specs:  
MIL-PRF-907E

Size	Part No.
1/2 lb. (227 grams)	03908
1 lb. (454 grams)	03910

*An extreme temperature lubricant for use in hostile environments and extreme temperatures.*



## ZeroTri Heavy-Duty Degreaser

- Fast evaporating
- Instant degreasing action
- Nonconductive
- Safe to use on most surfaces
- Ideal for degreasing metals
- Does not contain chlorinated solvents
- No residue
- Inverta Spray Valve allows one to spray in an upright or inverted position



*A moly-fortified extreme pressure lubricant that protects against seizure and heat-freeze.*

## All-Purpose Anti-Seize

- Prevents seizure up to 1800°F (982°C)
- Moly fortified
- Lead free
- Protects against seizure, heat-freeze, galling, rust and corrosion
- Lowers friction; reduces wrench torque
- Reduces maintenance costs
- Not affected by contraction, expansion or vibration
- Will not run, drip or settle out
- Steel blue color

Meets or exceeds these specs:  
MIL-PRF-907E

Size	Part No.
1/2 lb. (227 grams)	04108
1 lb. (454 grams)	04110



## Copper Anti-Seize

- Prevents seizure up to 1800°F (982°C)
- Lead free
- Protects against seizure, heat-freeze, galling, rust and corrosion
- Ideal for use on stainless steel and for joining dissimilar metals
- Brushes easily
- Highly adhesive on both wet and dry surfaces
- Cushions impact and shock loads
- "Copper plates" surfaces to prevent metal-to-metal contact
- Will not run, drip or settle out
- Copper color

Meets or exceeds these specs:  
MIL-PRF-907E



## HDX Heavy-Duty Degreaser

- Heavy-duty action removes oil, grease, wax, dirt, moisture, tar, brake fluid and other contaminants
- Nonflammable
- Fast evaporating
- Low odor
- Quick penetration
- No residue
- Nonconductive



## Anti-Spatter

- Excellent spatter protection provides cleaner welds
- Oversized nozzle for easy use with welding gloves
- Safe, water-based formula
- Nonflammable
- Does not contain suspect carcinogens such as methylene chloride
- Does not contain silicone
- Paint compatible
- Nontoxic

Size	Part No.
13 oz. (368 grams)	02116



## Instant Super Degreaser

- Heavy-duty performance
- Nonflammable
- Fast evaporating
- Nonconductive
- No residue
- Safe on metals
- Inverta Spray Valve allows one to spray in an upright or inverted position

Size	Part No.
20 oz. (567 grams)	00720

\*Not available in Canada



### TriFree Brake Cleaner

- Heavy-duty performance
- Instant degreasing action
- Improves brake performance
- No chlorinated solvents
- Helps stop disc brake squeal
- Fast evaporation
- Powerful jet spray
- Compliant to California V.O.C regulations
- No residue
- Nonconductive

Size	Part No.
15 oz. (425 grams)	03620



### Dry Film PTFE Lubricant

- Dry film will not attract dust or dirt
- Provides excellent lubrication
- Ideal for releasing molded parts
- Colorless, thin film
- Nonflammable
- Excellent for high temperature applications up to 500°F (260°C)
- Paintable
- Does not contain silicones
- Does not contain chlorinated solvents

Meets or exceeds these specs:  
Learjet LAS 1239

Size	Part No.
12 oz. (340 grams)	02616



### TKX All-Purpose Penetrant, Lubricant and Protectant

- Excellent all purpose lubricant
- Displaces moisture
- Loosens rusted or frozen parts
- Protects against corrosion
- High flash point of 175°F (79°C)
- Does not contain chlorinated solvents or silicones
- Nonconductive
- Safe on fabric, plastic, paint and other finishes
- Inverta Spray Valve allows one to spray in an upright or inverted position

Size	Part No.
11 oz. (312 grams)	02016
1 gal. (3.78 liters)	02028
5 gal. (18.93 liters)	02005
55 gal. (208 liters)	02055



### ThermaPlex Hi-Temp Bearing Grease

- Reduces risk of bearing failure at high temperatures
- Excellent high temperature performance
- Resists carbonization at high temperatures
- Extends relubrication intervals
- Very high dropping point
- Ensures optimal production rates
- Excellent vibration resistance
- Reduces grease consumption

Appearance: Brown colored paste  
Odor: Petroleum odor  
Temperature Range:  
-15°F (-22°C) to 392°F (200°C)  
Dropping Point: 536°F (280°C)  
NLGI Grade: No. 2  
4-Ball Weld Load: >400 kg.



### A-151 Solvent/Degreaser

- High flash point above 140°F (60°C)
- Low odor
- Controlled evaporation
- No residue
- No chlorinated solvents
- Nonconductive
- Safe to use on most surfaces
- Inverta Spray Valve allows one to spray in an upright or inverted position

Meets these requirements:  
Pratt & Whitney SPQP 208  
McDonnell Douglas CSD #1  
Boeing D6-17487 Rev. H  
Learjet LAS 1239



### LPS 2™ Industrial-Strength Lubricant

- Strong, multi-purpose lubricant and penetrant with added corrosion protection
- Provides a nondrying, light, oily film for use on indoor/outdoor equipment
- Reduces wear caused by friction and corrosion
- Displaces moisture
- Loosens rusted or frozen parts
- Provides up to one year of protection
- Nonconductive
- Safe on paint and most plastics
- Inverta Spray Valve allows one to spray in an upright or inverted position



### LPS 1™ Greaseless Lubricant

- Provides a dry, thin lubricating film
- Resists oil, dust and dirt build-up
- Fast acting penetration
- Displaces moisture
- Loosens rusted or frozen parts
- Provides a short term, light, corrosion resistant barrier
- Nonconductive
- Ideal for delicate mechanisms
- Used worldwide in aviation
- Safe on paint and most plastics
- Inverta Spray Valve allows one to spray in an upright or inverted position



### Instant Super Degreaser II

- Excellent degreaser for removing greases and oils
- Nonflammable
- Fast evaporating
- Does not contain chlorinated solvents
- Nonconductive
- No residue
- Safe on all metals
- Inverta Spray Valve allows one to spray in an upright or inverted position

*Meets or exceeds these specs:*  
McDonnell Douglas CSD #1  
Boeing D6-17487 Rev. H



### Heavy-Duty Silicone Lubricant

- Meets FDA regulation for incidental food contact
- Meets USDA requirements for H1
- Silicone-rich formula
- Water-based formula
- Colorless & odorless
- Ideal for rubber and plastic surfaces
- Eliminates sticking, binding and squeaking
- Does not contain chlorinated solvents
- Nonstaining
- Safe on most surfaces

*Meets or exceeds these specs:*  
FDA regulation 21 CFR 178.3570  
for Incidental Food Contact



### F-104<sup>o</sup> Fast Dry Solvent/Degreaser

- Heavy-duty degreaser
- 104°F (40°C) flash point
- Controlled evaporation
- Does not contain chlorinated solvents
- Safe to use on most surfaces
- Nonconductive
- No rinsing
- Minimal residue
- Inverta Spray Valve allows one to spray in an upright or inverted position

*Meets or exceeds these specs:*  
Airbus ABR 9-0140 Type I  
Boeing D6-17487 Rev. L  
LearJet 1239J  
Complies with the Aerospace NESHAP  
for wipe solvents



### Food Grade Silicone Lubricant

- Meets FDA regulation for incidental food contact
- Meets USDA requirements for H1
- Dry film will not attract dust or dirt
- Provides excellent lubrication
- Ideal for releasing molded parts
- Fast evaporating
- Excellent for high temperature applications up to 500°F (260°C)
- Does not contain chlorinated solvents
- Petroleum base

*Meets or exceeds these specs:*  
FDA regulation 21 CFR 178.3570  
for Incidental Food Contact

Size	Part No.
10 oz. (284 grams)	01716

**Great for FOOD PROCESSING and FOOD HANDLING applications.**



### Dry Film Silicone Lubricant

- Dry film will not attract dust or dirt
- Nonflammable
- Provides excellent lubrication
- Excellent for releasing molded parts
- Excellent for high temperature applications up to 500°F (260°C)
- Colorless, thin film
- Does not contain chlorinated solvents
- Petroleum base

Size	Part No.
12 oz. (340 grams)	01616



### ThermaPlex Hi-Load Bearing Grease

- Excellent load carrying ability
- Withstands shock loading
- Reduces wear from vibration
- Contains 3% moly
- Good corrosion resistance
- Excellent anti-wear properties
- Wide operating temperature range
- Reduces maintenance costs

*Appearance:* Black colored paste  
*Odor:* Petroleum odor  
*Temperature Range:*  
-22°F (-30°C) to 350°F (177°C)  
*Dropping Point:* 429°F (220°C)  
*NLGI Grade:* No. 2  
*4-Ball Weld Load:* >600 kg.  
*Timken "OK" Load:* 50 lbs.