

## TOKU IMPACT WRENCH



**MR-2207C - 1/4"**

- Compact and powerful
- Rubber covered ratchet head
- Durable ratchet head for long life
- Forward and reverse switch
- Ideal for confined work space



**MR-2209C - 3/8"**



**MR-2310B - 3/8"**

- Small body for easy grip handle and yet powerful
- Quick run down capacity
- Durable ratchet head for long life
- Forward and reverse switch
- Ideal for confined work space



**MR-2410B - 1"**

Specifications: Air Pressure 6kg/cm<sup>2</sup>

Torque: 1.0kg.m – 9.807Nm

Model	Square Drive (in)	Bolt Size (mm)	Torque Range (kg.m)	Max Torque (kg.m)	Net Weight (kg)	Overall Length (mm)	Free Speed (rpm)	Avg. Air Cons (m <sup>3</sup> /min)	Air Inlet (pt)
MR-2207C	1/4	8	0.6-2.8	5.5	0.53	165	250	0.35	1/4
MR-2209C	3/8	8	0.6-2.8	5.6	0.53	165	250	0.35	1/4
MR-2310B	3/8	10	1.4-7.0	8.3	1.13	254	180	0.45	1/4
MR-2410B	1/2	10	1.4-7.0	8.3	1.13	254	180	0.45	1/4



1/2"

1 - 7.233ft.lb

t	Hose Size (in)
	3/8
	3/8
	3/8
	3/8