

Quality Industrial Hoses

OIL & FUEL HOSE

5Delivery

Order No: SODH 150
150 psi W.P.
Meets AS 2683 & BS 3492
Tube: Black Synthetic Rubber
Reinforcement: High tensile synthetic
Cover: Black with Red Spiral Stripe
Temperature Range: -40°C +100°C
(-40°F +212°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
32	46
35	48
38	52
45	60
51	64
63	78
76	91

8Dock

Order No: SDH 250
250 psi W.P.
Meets BS 1435 Type S15
Tube: Black Synthetic Rubber
Reinforcement: High tensile synthetic, incorporating twin wire helix
Cover: Black Synthetic with Orange Longitudinal Stripe
Temperature Range: -40°C +100°C
(-40°F +212°F)

Minimum 4:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
76	98
102	126
152	182
203	237

6Suction

Order No: SOSD 150
150 psi W.P.
Meets AS 2683 & BS 3492
Tube: Black Synthetic Rubber
Reinforcement: High tensile synthetic, incorporating twin wire helix
Cover: Black Synthetic Rubber with Red Spiral Stripe
Temperature Range: -40°C +100°C
(-40°F +212°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
25	35
32	42
38	51
51	62
63	77
76	92
102	120
152	170
203	227

9Petrol Pump

Order No: SPPH 250
250 psi W.P.
Meets BS 3395 Type 1
Tube: Nitrile Rubber
Reinforcement: High tensile synthetic, incorporating twin wire helix
Cover: Black, Red or Green Nitrile Rubber
Temperature Range: -40°C +70°C
(-40°F +158°F)

Minimum 4:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
16	26
19	30
25	38

7Suction

Order No: SOSD 250
250 psi W.P.
Tube: Black Synthetic Rubber
Reinforcement: High tensile synthetic, incorporating twin wire helix
Cover: Black Synthetic Rubber with Orange Spiral Stripe
Temperature Range: -40°C +100°C
(-40°F +212°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
51	65
76	93
102	120
152	174
203	227

10Hot Tar/Asphalt

Order No: SHTA 150
150 psi W.P.
Tube: Nitrile Rubber
Reinforcement: High tensile synthetic, incorporating twin wire helix
Cover: Black Synthetic Rubber
Temperature Range: -40°C +210°C
(-40°F +410°F)

Minimum 4:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
38	58
51	71
63	84
76	95
102	123

OIL & FUEL HOSE

11Welding Hose

Order No: SWGH 150
150 psi W.P.
Tube: Black Synthetic Rubber
Reinforcement: High tensile synthetic
Cover: Red Synthetic Rubber
Temperature Range: -40°C +100°C
(-40°F +212°F)

Minimum 4:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
5	11
6	12
8	15
10	17

12Welding Hose

Order No: SWGH 300
300 psi W.P.
Tube: Black Synthetic Rubber
Reinforcement: High tensile synthetic
Cover: Blue Synthetic Rubber
Temperature Range: -40°C +100°C
(-40°F +212°F)

Minimum 4:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
5	14
6	14
8	17
10	19

AIR HOSE

1Standard

Order No: SAH 150
150 psi W.P.
Meets BS 5118 Type 1
Tube: Oil mist resistance Rubber
Reinforcement: High tensile synthetic
Cover: Black Synthetic with Blue Spiral Stripe
Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
6	13
10	18
13	21
16	24
19	29
25	36
32	43
38	50
51	65
63	78
76	91
102	118

2Super

Order No: SAH 300
300 psi W.P.
Meets BS 5118 Type 2
Tube: Oil mist resistance Rubber
Reinforcement: High tensile synthetic
Cover: Yellow Synthetic
Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
32	44
38	52
51	66
76	94
102	121

3Steel

Order No: SAH 600
600 psi W.P.
Tube: Oil mist resistance Rubber
Reinforcement: High tensile Steel cords
Cover: Yellow Synthetic
Temperature Range: -40°C +120°C
(-40°F +248°F)

Minimum 4:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
19	31
25	38
32	45
38	56
51	69
63	81
76	95
102	120

4Multiservice

Order No: SSMH 300
300 psi W.P.
Tube: Nitrile Rubber
Reinforcement: High tensile synthetic
Cover: Red Synthetic
Temperature Range: -30°C +100°C
(-22°F +212°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
6	13
10	18
13	21
16	24
19	29
25	36
32	44
38	52
51	66

17Air Brake

Order No: SABH 250
250 psi W.P.
Tube: Specially compounded to meet requirements of SAE J1402
Reinforcement: High tensile synthetic
Cover: Black Synthetic Rubber
Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 4:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
10	19
13	21

CHEMICAL HOSE

18Suction

Order No: SXLPE 150
150 psi W.P.
Tube: XLPE
Reinforcement: High tensile synthetic, incorporating wire helix
Cover: Green Synthetic Rubber
Temperature Range: -40°C +70°C
(-40°F +158°F)

Minimum 6:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
25	41
32	48
38	54
51	67
63	81
76	95
102	120

STEAM HOSE

13Standard

Order No: SSH 100
100 psi W.P.
Tube: EPDM Rubber
Reinforcement: High tensile synthetic
Cover: Black EPDM Rubber
Temperature Range: -40°C +170°C
(-40°F +338°F)

Minimum 10:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
19	36
25	42
32	48
38	55
44	62
51	67

14Steel

Order No: SSH 250
250 psi W.P.
Meets BS 5342 & 1985 Type 2
Tube: EPDM Rubber
Reinforcement: Steel wire cords
Cover: Red Synthetic Rubber
Temperature Range: -30°C +236°C
(-22°F +456°F)

Minimum 10:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
13	25
19	32
25	39
32	46
38	54
51	67
63	83
76	95
102	124

15W.S.G.P.

Order No: SSH 80
80 psi W.P.
Tube: Natural Rubber – Meet F.D.A. Requirements
Reinforcement: High tensile synthetic
Cover: White Synthetic Rubber
Temperature Range: -40°C +153°C
(-40°F +310°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
19	33
25	39

16Furnace Door

Order No: SFND 200
200 psi W.P.
Tube: Black Synthetic Rubber
Reinforcement: High tensile synthetic
Cover: Fibreglass impregnated with heat and flame resistant synthetic rubber
Temperature Range: -40°C +121°C
(-40°F +250°F)

Minimum 4:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
19	31
25	39
32	49
38	55
51	71
76	100

MATERIALS HANDLING

21 Delivery

Order No: SCDH 150
150 psi W.P.

Tube: Black Synthetic Rubber,
Antistatic

Reinforcement: High tensile synthetic
Cover: Black Synthetic with Green
Spiral Stripe

Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
76	95
102	122
127	149
152	174

22 Suction


Order No: SCSD 150
150 psi W.P.

Tube: Black Synthetic Rubber

Reinforcement: High tensile synthetic
incorporating wire helix
Cover: Black Synthetic with Green
Spiral Stripe

Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
76	98
102	124
127	152
152	174

23 Grouting

Order No: SBT 600
600 psi W.P.

Tube: Black Synthetic Rubber

Reinforcement: High tensile synthetic
Cover: Black Synthetic Rubber

Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
51	68
63	83
76	100
102	130

24 Sand Blast

Order No: SBH 150
150 psi W.P.

Tube: Black Synthetic Rubber,
Antistatic

Reinforcement: High tensile synthetic
Cover: Black Synthetic Rubber with
Green Spiral Stripe

Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
25	35
32	48
38	56
51	68

WATER HOSE

25 Delivery

Order No: SWDH 150
150 psi W.P.

Tube: Natural Rubber

Reinforcement: High tensile synthetic
Cover: Black Synthetic with Yellow
Spiral Stripe

Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
32	44
38	50
51	62
63	75
76	87
102	110
127	143
152	168

26 Suction

Order No: SWSD 150
150 psi W.P.

Meets BS 1102

Tube: Natural Rubber

Reinforcement: High tensile synthetic,
incorporating wire helix
Cover: Black Synthetic with Yellow
Spiral Stripe

Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
25	35
32	43
38	50
51	63
63	77
76	89
102	118
127	145
152	171
203	227
254	276

27 Hot Wash

Order No: SHW 300
300 psi W.P.

Meets BS 1435 Type S15

Tube: Specially Compounded Rubber

Reinforcement: High tensile synthetic
Cover: White Synthetic Rubber
Temperature Range: -40°C +100°C
(-40°F +212°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
19	30
25	36

28 Tank Cleaning

Order No: STCH 350
350 psi W.P.

Tube: Specially Compounded
Rubber

Reinforcement: High tensile synthetic,
incorporating two stainless steel anti-
static wires

Cover: Black Specially Compounded
Rubber with Yellow Marking Rings

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
38	54
51	68

FOOD & BEVERAGE HOSE

19 Brewers Delivery

Order No: SBDH 150
150 psi W.P.

Tube: Red Natural Rubber
Meet F.D.A. Requirements

Reinforcement: High tensile synthetic,
incorporating twin wire helix
Cover: Red Natural Rubber

Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
25	40
38	53
51	65
76	91
102	118

20 Brewers Suction & Delivery

Order No: SBSH 150
150 psi W.P.

Tube: Red Natural Rubber
Meet F.D.A. Requirements

Reinforcement: High tensile synthetic,
incorporating wire helix
Cover: Red Natural Rubber

Temperature Range: -40°C +85°C
(-40°F +185°F)

Minimum 3:1
Safety Factor



Normal Bore (mm)	Outside Diameter (mm)
25	41
38	54
51	66
76	93
102	121