

## Chain Block



Capacity (tons)	Standard Lift (m)	Minimum Distance Between Hooks (mm)	Net Weight (kg)
1/2	2.5	285	8.4
1	2.5	315	11.0
1 1/2	2.5	340	13.5
2	3.0	380	21.0
3	3.0	475	24.0
5	3.0	600	40.0
7 1/2	3.5	700	59.0
10	3.5	740	76.0

## Wire Rope Winch



### Specifications:

Model No.	ET-15	ET-30
Lifting Capacity	1,500 kgs.	3,000 kgs.
Pulling Capacity	2,500 kgs.	5,000 kgs.
Standard Length Cable	20 meters	20 meters.
Steel Wire Cable	6×25(Fi) IWRC	6×25(Fi)IWRC
	9mm diameter	14 mm diameter
Handle Length	1,040 mm	1,210 mm
Pull on Handle for Full Load	38 kgs.	42 kgs.
Net Weight less wire cable	10 kgs.	21 kgs.
Dimension	550 × 290 × 110mm	670 × 300 × 150 mm
Material (casing)	SS41 (JIS)	SS41 (JIS)
Shearing of shear pins	2,800 kgs.	5,500 kgs.
Breaking Load of Wire Cable	5,430 kgs.	11,200 kgs.
Speed of Movement	1 to 3 meters/Min.	1 to 3 meters/Min.