

AI Type of Shackles

CHAIN SHACKLES ROUND PIN—SCREW PIN

K-G-100
K-S-100



K-N-G-100
K-N-S-100



New
Type

Screw pin chain shackles meet
Federal Specification
RR-C-271b Type IV Class 2

K-G-105
K-S-105



Round pin chain shackles meet
Federal Specification
RR-C-271b Type IV Class 5.

Safe Working Load-Tons	DIMENSIONS IN INCHES							Weight Pounds Each
	Size Inches	Inside Length	Inside Width	Diameter		Tolerance Plus or Minus		
				Pin	Outside of Eye	Length	Width	
1/2	3/4	3/8	3/8	3/8	3/8	3/8	3/8	0.11
3/4	3/4	1 1/8	3/8	3/8	3/8	3/8	3/8	0.17
1	3/4	1 1/4	3/8	3/4	3/8	3/8	3/8	0.29
1 1/2	3/4	1 3/4	3/8	1/2	1 1/4	3/8	3/8	0.42
2	1/2	1 5/8	3/8	3/8	1 3/8	3/8	3/8	0.68
3 1/4	3/4	2	1 1/4	3/4	1 5/8	3/8	3/8	1.21
4 3/4	3/4	2 3/8	1 1/4	3/4	1 7/8	3/4	3/8	2.14
6 1/2	3/4	2 3/4	1 3/4	1	2 1/8	3/4	3/8	3.1
8 1/2	1	3 3/4	1 3/4	1 1/8	2 3/8	3/4	3/8	4.5
9 1/2	1 1/8	3 3/4	1 3/4	1 1/4	2 3/8	3/4	3/8	6.6
12	1 1/4	3 3/4	2 1/8	1 3/8	3	3/4	3/8	8.9
13 1/2	1 3/8	4 3/4	2 1/4	1 1/2	3 3/8	3/4	3/8	12
17	1 1/2	4 3/4	2 3/8	1 5/8	3 3/8	3/4	3/8	16.2
25	1 3/4	5 3/4	2 3/8	2	4 3/8	3/4	3/8	25
35	2	6 3/4	3 1/4	2 1/4	5	3/4	3/8	36
50	2 1/2	8	4 1/8	2 3/4	6	3/4	3/8	74
* 75	3	8 1/2	5	3 1/4	6 1/2	3/4	3/8	108

* Furnished in round pin only.

BOLT TYPE ANCHOR & CHAIN SHACKLES

Safe Working Load-Tons	DIMENSIONS IN INCHES								Weight Pounds Each	
	Size Inches	Inside Length		Inside Width at Pin	Diameter		Tolerance Plus or Minus		1130	1150
		1130	1150		Pin	Outside of Eye	Length	Width		
2	1/2	1 1/8	1 5/8	3/8	3/8	1 3/8	3/8	3/8	0.82	0.76
3 1/4	3/4	2 3/8	2	1 1/4	3/4	1 5/8	3/8	3/8	1.58	1.56
4 3/4	3/4	2 3/4	2 3/8	1 1/4	3/8	1 7/8	3/4	3/8	2.82	2.62
6 1/2	3/4	3 3/4	2 3/4	1 3/4	1	2 1/8	3/4	3/8	3.95	3.65
8 1/2	1	3 3/4	3 3/8	1 3/4	1 1/8	2 3/8	3/4	3/8	5.6	5.35
9 1/2	1 1/8	4 3/4	3 3/8	1 3/4	1 1/4	2 3/8	3/4	3/8	7.85	7.27
12	1 1/4	4 3/4	3 3/8	2 1/8	1 3/8	3	3/4	3/8	11.2	10.2
13 1/2	1 3/8	5 1/4	4 3/8	2 1/4	1 1/2	3 3/8	3/4	3/8	15.2	13.35
17	1 1/2	5 3/4	4 3/8	2 3/8	1 5/8	3 3/8	3/4	3/8	19.5	18.5
25	1 3/4	7	5 3/4	2 3/8	2	4 3/8	3/4	3/8	31.3	28.5
35	2	7 3/4	6 3/4	3 1/4	2 1/4	5	3/4	3/8	46.3	41.1
50	2 1/2	10 1/2	8	4 1/8	2 3/4	6	3/4	3/8	94	84.5
75	3	13	8 1/2	5	3 1/4	6 1/2	3/4	3/8	145	123
100	3 1/2	15	10 1/2	5 3/4	3 3/4	8	1	3/4	250	218
130	4	17	12	6 1/2	4 1/4	9	1	3/4	358	310
150	4 3/8	18 1/4	14 1/2	7 1/4	5 1/8	10 3/8	1	3/4	525	460
200	5	19	16 1/2	8 1/4	5 3/8	10 3/8	1	3/4	664	609

K-G-1130
K-S-1130



Bolt type anchor shackles with thin head bolt — nut with cotter pin. Meets Federal Specification RRC-271b Type IV Class 6.

K-G-1150
K-S-1150



Bolt type chain shackles. Thin hex head bolt — nut with cotter pin.